NSN 5320-01-123-6466



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-123-6466 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.911 inches and 0.951 inches **Head Style:** Err-090 **Head Height:** Between 0.061 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.398 inches and 0.413 inches Lubrication: Dry film **Grip Length:** Between 0.501 inches and 0.562 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 156000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-123-6466

Pin-rivet - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A528u0