NSN 5320-01-123-9943



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-123-9943 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.535 inches and 0.575 inches **Head Style:** Err-090 **Head Height:** Between 0.042 inches and 0.050 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.298 inches and 0.312 inches Lubrication: Dry film **Grip Length:** Between 0.189 inches and 0.250 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-123-9943

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0