

View Online at <https://aerobasegroup.com/nsn/5320-01-124-7740>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.848 inches and 0.868 inches

Head Style:

Err-090

Head Height:

Between 0.079 inches and 0.086 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.298 inches and 0.312 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.501 inches and 0.562 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4458 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.