

View Online at <https://aerobasegroup.com/nsn/5320-01-124-7741>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.911 inches and 0.931 inches

Head Style:

Err-090

Head Height:

Between 0.104 inches and 0.111 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.398 inches and 0.413 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.501 inches and 0.562 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4458 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.