## NSN 5320-01-125-1268

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-125-1268

Fastener Length:
1.678 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.386 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 1.469 inches and 1.532 inches
Hardness Rating:
48.0 rockwell c and 53.0 rockwell c stem
Shear Strength:
112000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 8740 stem
Material Specification:
Astm a547 assn standard 1st material response or 66 federal standard all material responses or mil-s-6758 military specification 3rd
material response sleeve
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-s-6049 spec.