NSN 5320-01-126-1675

Pin-rivet - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5320-01-126-1675
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Bronze
Fastener Length:
Between 3.447 inches and 3.467 inches
Head Style:
Err-090
Head Height:
Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.387 inches and 0.412 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 3.057 inches and 3.067 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color bronze
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Surface Treatment:
Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

NSN 5320-01-126-1675

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0
Mil-std (military Standard):

Mil-s-5000 spec.