NSN 5320-01-129-0689

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-129-0689 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.370 inches and 1.390 inches **Head Style:** Err-090 Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.6335 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.880 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-129-0689

Pin-rivet - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A528u0