NSN 5320-01-129-0690

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-129-0690 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.433 inches and 1.453 inches **Head Style:** Err-090 Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style: Head Major Diameter:** 0.6335 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.943 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

NSN 5320-01-129-0690

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0