# NSN 5320-01-129-0692

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-129-0692



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.557 inches and 1.577 inches

## Head Style:

Err-090

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

# Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.6335 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.067 inches

Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

160000 pounds per square inch

## **Thread Size:**

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

# Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-129-0692

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

