# NSN 5320-01-129-0695

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-129-0695



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.015 inches and 1.035 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

0.630 inches

# Thready Qty Per Inch (tpi):

28

### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.250 inches

# Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-129-0695

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

