NSN 5320-01-129-2217

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-129-2217 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.947 inches and 0.967 inches **Head Style:** Err-090 Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** 0.3948 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** 0.567 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Fluted threads Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-129-2217

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0