

View Online at <https://aerobasegroup.com/nsn/5320-01-129-4525>

**Fastener Length:**

0.470 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.156 inches and 0.160 inches

**Head Major Diameter:**

Between 0.282 inches and 0.290 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.065 inches and 0.125 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.