
# NSN 5320-01-130-0636

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.490 inches and 1.510 inches

## Head Style:

Err-090

### **Head Height:**

Between 0.098 inches and 0.112 inches

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3110 inches and 0.3120 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.472 inches and 0.502 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.995 inches and 1.005 inches

## Thready Qty Per Inch (tpi):

24

# Thread Size:

0.312 inches

# **Special Features:**

One collar included

# Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

# Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

# Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

# NSN 5320-01-130-0636

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

