# NSN 5320-01-131-9909

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-131-9909



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.740 inches and 0.760 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

### **End Application:**

Aircraft, hornet f/a-18, f/a-18e/f hornet aircraft, aircraft, harrier av-8b

### Grip Length:

0.255 inches

### Thready Qty Per Inch (tpi):

24

### Thread Size:

0.312 inches

# Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

#### Material Specification:

Ams 5629 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-131-9909

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

