

View Online at <https://aerobasegroup.com/nsn/5320-01-131-9910>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.990 inches and 1.010 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.068 inches and 0.078 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Solid film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.505 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

44.0 rockwell c and 50.0 rockwell c

**Thread Size:**

0.312 inches

**Shear Strength:**

125000 single pounds per square inch

**Special Features:**

6-32unjc-3b thread size along the longitudinal axis from the head end, 0.120 in. Slot length, 0.060 in. Slot width located on shank near head

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0