NSN 5320-01-131-9918

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-131-9918 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.690 inches and 0.710 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Unable To Decode:** Unable to decode and unable to decode **Unable To Decode:** Unable to decode and unable to decode **Grip Length:** 0.380 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Special Features:** 0.325 in. Thread length on stud end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-131-9918

Pin-rivet - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0