NSN 5320-01-132-0547

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-132-0547 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.771 inches and 0.796 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3897 inches **Head Major Diameter:** 0.583 inches Tip Diameter: 0.3854 inches Lubrication: Cetyl alcohol and dry film **Grip Length:** 0.380 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1724 professional/industrial association standard

Shelf Life: N/a

NSN 5320-01-132-0547

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0