

View Online at <https://aerobasegroup.com/nsn/5320-01-132-1117>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Err-090

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.3304 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.443 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0