## NSN 5320-01-132-2225

Pin-rivet - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-132-2225 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.677 inches and 0.697 inches **Head Style:** Err-090 Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.2612 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F/a-18e/f hornet aircraft, aircraft, eagle f-15, aircraft, hornet f/a-18 **Grip Length:** 0.380 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjc

## NSN 5320-01-132-2225

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0