

View Online at <https://aerobasegroup.com/nsn/5320-01-132-4441>

**Fastener Length:**

Between 0.536 inches and 0.566 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.154 inches and 0.159 inches

**Shank Style:**

Self-plugging

**Head Major Diameter:**

0.270 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.251 inches and 0.375 inches

**Countersink Angle:**

Between 118.5 degrees and 121.5 degrees

**Material:**

Steel comp 1006 mandrel or steel comp 1008 mandrel or steel comp 1009 mandrel or steel comp 1010 mandrel or steel comp 1011 mandrel or steel comp 1012 mandrel or steel comp 1013 mandrel or steel comp 1015 mandrel or steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel or steel comp 1023 mandrel or steel comp 1524 mandrel or steel comp 1025 mandrel

**Surface Treatment:**

Zinc mandrel and chromate mandrel or cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response body or mil-c-5541 military specification single treatment response body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.