NSN 5320-01-132-8638

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-132-8638 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.003 inches and 1.023 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** Aircraft, eagle f-15; aircraft, hornet f/a-18; f/a-18e/f hornetaircraft **Grip Length:** 0.693 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-132-8638

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0