

View Online at <https://aerobasegroup.com/nsn/5320-01-133-3954>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.635 inches and 0.655 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.255 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Product Name:

(navy) pin - rivet, threaded, shear, protruding head, hex point drive

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0