# NSN 5320-01-133-4908

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-133-4908

# Head Style:

Flush countersunk

## Shank Diameter:

Between 0.1880 inches and 0.1895 inches

## Shank Style:

Pin-rivet, multiple grooved

## Head Major Diameter:

0.332 inches

Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.439 inches and 0.500 inches

## **Features Provided:**

Casehardened

#### Min. Tensile Strength (psi):

180000 pounds per square inch

#### Hardness Rating:

78.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

## Shear Strength:

108000 single pounds per square inch

## Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 8740

## **Material Specification:**

Aisi assn standard single material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

## **Specification Data:**

80205-nas7026 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A528u0