NSN 5320-01-133-4910

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-133-4910 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.823 inches and 0.843 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.443 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color green on thread end Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-133-4910

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0