## NSN 5320-01-133-7300

Blind Rivet - Page 1 of 1

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-133-7300

Fastener Length:
Between 0.299 inches and 0.319 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.172 inches and 0.176 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.290 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.126 inches and 0.187 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating
visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.
Material:
Steel comp 8740 stem
Material Specification:
Qq-a-430 federal specification single material response sleeve
Surface Treatment:
Cadmium stem and chromate stem
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):