

View Online at <https://aerobasegroup.com/nsn/5320-01-133-8675>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.428 inches and 0.448 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.055 inches and 0.060 inches

**Width Between Flats:**

Between 0.0635 inches and 0.0645 inches

**Shank Diameter:**

Between 0.1630 inches and 0.1635 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.306 inches and 0.322 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.120 inches and 0.130 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.164 inches

**Shear Strength:**

95000 single pounds per square inch

**Criticality Code Justification:**

Aaze and aatb

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0