# NSN 5320-01-133-9520

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-133-9520



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.010 inches and 1.030 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

# Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# End Application:

W/s: aviation ordance; f117a aircraft; gun system, 25mm; aircraft, harrier av-8b; aircraft, b-1b

# Grip Length:

0.630 inches

Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

# **Thread Size:**

0.250 inches

#### **Countersink Angle:**

100.0 degrees

### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-133-9520

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

