NSN 5320-01-134-0785

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-134-0785 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.565 inches and 0.585 inches **Head Style:** Err-090 Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3016 inches Lubrication: Solid film or cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield iii, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-134-0785

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0