NSN 5320-01-134-8770

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-134-8770 **Head Style:** Hexagon **Head Height:** 0.190 inches **Shank Diameter:** Between 0.3725 inches and 0.3745 inches Shank Style: Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 0.970 inches and 1.031 inches Width Across Flats: Between 0.491 inches and 0.500 inches **Hardness Rating:** 39.0 rockwell c nut and 43.0 rockwell c nut Material: Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve **Specification Data:** 80205-nas1669 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.