# NSN 5320-01-135-5539

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-135-5539



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.503 inches and 0.523 inches

## Head Style:

Err-090

### Head Height:

Between 0.064 inches and 0.074 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.357 inches and 0.377 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Unable To Decode:

Unable to decode and unable to decode

## Unable To Decode:

Unable to decode and unable to decode

## Grip Length:

0.193 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.190 inches

## **Special Features:**

0.325 in. Thread length on stud end

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-01-135-5539

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

