NSN 5320-01-136-7163

Blind Rivet - Page 1 of 1

Mil-c-5541 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-136-7163

| view Online at https://aerobasegroup.com/hist//3020-01-130-7100 |
|--|
| Fastener Length: |
| Between 0.318 inches and 0.338 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.200 inches and 0.204 inches |
| Shank Style: |
| Self-plugging mechanically locked stem |
| Head Major Diameter: |
| 0.357 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.126 inches and 0.187 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Special Features: |
| Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating |
| visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. |
| Material: |
| Steel comp 8740 stem |
| Material Specification: |
| Qq-a-430 federal specification single material response sleeve |
| Surface Treatment: |
| Cadmium stem and chromate stem |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |