

View Online at <https://aerobasegroup.com/nsn/5320-01-140-9934>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.427 inches and 0.447 inches

Head Style:

Straight pan

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

Grip Length:

0.130 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

125000 single pounds per square inch

Product Name:

(inavy) pin - rivet, threaded, shear, protruding head, hex point drive

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0