## NSN 5320-01-141-1871

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-141-1871

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.896 inches and 0.921 inches
Head Style:
Err-090
Head Height:
Between 0.082 inches and 0.094 inches
Shank Diameter:
0.3912 inches
Head Major Diameter:
Between 0.567 inches and 0.581 inches
Tip Diameter:
0.3828 inches
Lubrication:
Cetyl alcohol and dry film
Grip Length:
Between 0.490 inches and 0.505 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1728 professional/industrial association standard
Shelf Life:

N/a

## NSN 5320-01-141-1871

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0