

View Online at <https://aerobasegroup.com/nsn/5320-01-141-1874>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.065 inches and 1.085 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.295 inches and 0.315 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corporation and dry film

**Grip Length:**

0.755 inches

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Product Name:**

(inavy) pin - riqvet, threaded, shear, protruding head, hex point drive

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Ti-shield iii, fscm 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0