# NSN 5320-01-141-5599

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-141-5599



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.802 inches and 0.822 inches

## Head Style:

Err-090

#### Head Height:

Between 0.055 inches and 0.065 inches

## Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.306 inches and 0.322 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and dry film

## End Application:

W/s: aircraft, hornet f/a-18; f/a-18e/f hornet aircraft; aircraft, eagle f-15

#### Grip Length:

0.505 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

# Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Anodize

# Surface Treatment Specification:

Ti-shield iii, fscm 73197 mfr ref single treatment response

# Thread Series Designator:

Unjc

#### Shelf Life:

N/a

# NSN 5320-01-141-5599

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

