# NSN 5320-01-142-1558

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-142-1558



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.385 inches and 1.405 inches

# Head Style:

Err-090

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.5066 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and dry film

# Grip Length:

1.005 inches

# Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

#### Surface Treatment Specification:

Ti-shield iii fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-142-1558

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

