NSN 5320-01-142-3229

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5320-01-142-3229

· actoric · zong
Between 0.520 inches and 0.545 inches
Head Style:
Err-090
Head Height:
Between 0.044 inches and 0.056 inches
Shank Diameter:
0.2010 inches
Head Major Diameter:
Between 0.302 inches and 0.312 inches
Tip Diameter:
0.1977 inches
Lubrication:
Cetyl alcohol and dry film
Grip Length:
Between 0.240 inches and 0.255 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1728 professional/industrial association standard
Shelf Life:
N/a

NSN 5320-01-142-3229

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0