# NSN 5320-01-142-3240

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-142-3240



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.565 inches and 1.585 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

## **End Application:**

W/s: aircraft, hornet f/a-18; f/a-18e/f hornet aircraft

#### Grip Length:

1.255 inches

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

#### Surface Treatment Specification:

Ti-shield iii mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-142-3240

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

