NSN 5320-01-142-3242

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-142-3242 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.240 inches and 1.260 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** 0.1465 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style: Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 44.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** 6-32unjc-3b thread size along the longitudinal axis from the head end; 0.120 in. Slot length, 0.060 in. Slot width located on shank near head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response

N/a

Unjf

Shelf Life:

Thread Series Designator:

NSN 5320-01-142-3242

Pin-rivet - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0