NSN 5320-01-142-3583



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-142-3583 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.871 inches and 0.896 inches **Head Style:** Flush countersunk **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.494 inches **Tip Diameter:** 0.3189 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.490 inches and 0.505 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Thread Size: 0.3125 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 8-32unjc-3b thread size, 0.320 in. Length along the longitudinal axis from the head end, 0.120 in. Slot length, 0.060 in. Slot width located 0.260 in. From top of head to center of slot Steel comp xm-13

Material: **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-142-3583

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0