## NSN 5320-01-142-4899

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Head Style:** 

**Thread Direction:** 

Fastener Length:

Between 0.896 inches and 0.921 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-142-4899

Err-090
Head Height:
Between 0.082 inches and 0.094 inches
Shank Diameter:
0.4068 inches
Head Major Diameter:
Between 0.582 inches and 0.596 inches
Tip Diameter:
0.3984 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 0.490 inches and 0.505 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1729 professional/industrial association standard
Shelf Life:
N/a

## NSN 5320-01-142-4899

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0