NSN 5320-01-142-4899

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-142-4899



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.896 inches and 0.921 inches

Head Style:

Err-090

Head Height:

Between 0.082 inches and 0.094 inches

Shank Diameter:

0.4068 inches

Head Major Diameter:

Between 0.582 inches and 0.596 inches

Tip Diameter:

0.3984 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

Between 0.490 inches and 0.505 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1729 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-142-4899

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

