## NSN 5320-01-142-4900

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-142-4900 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.928 inches and 0.948 inches **Head Style:** Err-090 Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.6335 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film **End Application:** W/s: aircraft, harrier av-8b; aircraft, hornet f/a-18 **Grip Length:** 0.443 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield iii fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-142-4900

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0