NSN 5320-01-143-6730

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-143-6730



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.925 inches and 0.945 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

0.1098 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2802 inches and 0.2807 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.5066 inches

Lubrication:

Solid film or dry film and cetyl alcohol

Grip Length:

0.505 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-143-6730

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

