

View Online at <https://aerobasegroup.com/nsn/5320-01-144-1696>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.897 inches and 0.917 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

Grip Length:

0.317 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Product Name:

(inavy) pin - riquet, threaded, shear, protruding head, hex point drive

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield iii mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0