# NSN 5320-01-144-2279

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-144-2279



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.881 inches and 0.906 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

0.4726 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.711 inches

## Tip Diameter:

0.4675 inches

## Lubrication:

Dry film and cetyl alcohol

### Grip Length:

Between 0.427 inches and 0.442 inches

# Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Thread Size:**

0.438 inches

#### Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp xm-13

#### Material Specification:

Ams 5629 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-144-2279

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

