

View Online at <https://aerobasegroup.com/nsn/5320-01-144-4783>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.440 inches and 0.460 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

0.0955 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.3813 inches

Lubrication:

Solid film or dry film and cetyl alcohol

Grip Length:

0.130 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield iii mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0