NSN 5320-01-144-4783

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-144-4783

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 0.440 inches and 0.460 inches |
| Head Style: |
| Countersunk w/reverse chamfer |
| Head Height: |
| 0.0955 inches |
| Width Between Flats: |
| Between 0.0791 inches and 0.0806 inches |
| Shank Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| 0.3813 inches |
| Lubrication: |
| Solid film or dry film and cetyl alcohol |
| Grip Length: |
| 0.130 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Thread Size: |
| 0.190 inches |
| Shear Strength: |
| 95000 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Ti-shield iii mfr ref single treatment response |
| Thread Series Designator: |

Unjf

NSN 5320-01-144-4783

Pin-rivet - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0