# NSN 5320-01-144-5691

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-144-5691

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.708 inches and 0.733 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

0.4053 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.598 inches

## Tip Diameter:

0.4023 inches

#### Lubrication:

Dry film and cetyl alcohol

## Grip Length:

Between 0.302 inches and 0.317 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Thread Size:

0.375 inches

## Shear Strength:

125000 single pounds per square inch

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No



# NSN 5320-01-144-5691

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

