NSN 5320-01-145-5500

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-145-5500



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.240 inches and 1.260 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

0.1465 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and dry film

Grip Length:

0.750 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

210000 pounds per square inch

Hardness Rating:

44.0 rockwell c and 50.0 rockwell c

Thread Size:

0.312 inches

Countersink Angle:

100.0 degrees

Special Features:

6-32unjc-3b thread size along the longitudinal axis from the head end; 0.120 in. Slot length, 0.060 in. Slot width located on shank near head

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-145-5500

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

